

MA300-BT

Metallic Casing Outdoor Access Control



MA300-BT, one of the innovative biometric fingerprint readers for access control applications. Offering unparalleled performances by adopting an advanced ZK fingerprint algorithm for reliability, precision and excellent matching speed.

It is metallic casing and IP65 rated which enables it to be resistant from water, dust and other outside damages.

MA300-BT offers the flexibility to be installed standalone or with any third party panels that support 26-bit wiegand. User can be enrolled by the administrator card when the device works in standalone mode.TCP/IP and RS485 are available, so that the device can be connected easily and conveniently.

It supports Bluetooth communication, mobile phone App management, And realizes access control, user information registration, devices setting up.



Rugged Structure and Extra Durability

 IP65 rated waterproof and dustproof structure



Metallic Casing

 Vandal-proof for outdoor installation



Fast and Accurate Fingerprint Algorithm

- 1 touch a-second user recognition
- Store 1,500 templates, 10,000 cards and 100,000 transactions



Easy Installation and Connectivity

- Wiegand input & output
- Network interface by TCP/IP or RS485



Full Access Control Features

- Anti-passback
- Access control interface for 3rd party electric lock, door sensor, exit button, alarm and doorbell



Bluetooth Communication

- Mobile phone App Management
- Access control, user information registration and devices setting up

Specifications

·	
Fingerprint Capacity	1,500 templates
Card Capacity	10,000
Transaction Capacity	100,000
Hardware Platform	ZEM720
Sensor	ZK Optical Sensor
Algorithm Version	ZK Finger v10.0
Communication	RS485,TCP/IP,USB-host,Bluetooth
Interfaces for Access Control	3rd party electric lock, door sensor, exit button, alarm
Wiegand Signal	Input & Output
Standard Access Control Function	RS485 Reader, Time Zone, Group, Multi-identification, Duress mode, Anti-passback
Optional Functions	Mifare, external USB keypad
Display	N/A
Power Supply	12V DC
Operating Temperature	-10 °C- 60 °C
Operating Humidity	10% -90%
Protection Grade	IP65
Dimension(W×H×D)mm	73×148×34.5
Gross Weight	1.15kg

Optional Accessories







Exit Button RS485 Reader

485 Reader Electric Lock







Alarm

Sensor

Configuration







Dimensions (mm)



ZKBioBT APP Download



Scan the following QR code with your mobile phone, and download and install the APP. Mobile phone requirement for APP installation: Andriod OS later than version 4.3, compliant with the Bluetooth protocol later than 7.1, devices later than iphone 4s.



V1.0 2019.11.22